

- Deeply rounded surfaces combine to create the enduring appeal of stone cobbles formed by glaciers and set by hand
- Designed to be installed in a random runner or ashlar pattern, with stones of various, modulating lengths and widths
- Suitable for medium vehicular applications, such as residential streets and commercial parking lots, with proper pavement design and installation
- Joints and surfaces are designed to create a natural look, minimize furniture wobble, and meet ADA gap and lippage requirements
- Made of durable concrete that won't decay, distort, or attract pests. Iron oxide pigments won't fade with extended UV exposure. Meets or exceeds applicable requirements of ASTM C936 and C1782

STONE(S)


NOTES

,						
				Twinkie	Square	Rec
	Height	in	ln.	2.36	2.36	2.36
		mm	MM.	60	60	60
	Length	in	IN.	2.24	4.53	6.77
		mm	MM	57	115	172
	Width	in	IN	4.53	4.53	4.53
		mm	MM	115	115	115
	Units	/pl	QTY	90	270	240

Weights are approximate and do not include shipping pallet. Installation to applicable ICPI standards is required for warranty coverage. Made with natural

materials, which vary in color, and Portland cement, which may effloresce - any

PALLET LAYOUT



PALLET SPECS Pallet Weight 2744 lbs Sq Ft/Pallet 98 sq.ft.



implied warranty to the contrary is disclaimed.






- Deeply rounded surfaces combine to create the enduring appeal of stone cobbles formed by glaciers and set by hand
- Barreled sidewalls are ideal for decorative curvilinear laying patterns such as fans and circles
- Suitable for medium vehicular applications, such as residential streets and commercial parking lots, with proper pavement design and installation
- Joints and surfaces are designed to create a natural look, minimize furniture wobble, and meet ADA gap and lippage requirements
- Made of durable concrete that won't decay, distort, or attract pests. Iron oxide pigments won't fade with extended UV exposure. Meets or exceeds applicable requirements of ASTM C936 and C1782

STONE(S)

				•	
				Square	
	Height	in	ln.	2.36	
		mm	MM.	60	
	Length	in	IN.	4.53	
		mm	MM	115	
	Width	in	IN	4.53	
		mm	MM	115	
	Units	/pl	QTY	700	

PALLET LAYOUT



NOTES

Weights are approximate and do not include shipping pallet. Installation to applicable ICPI standards is required for warranty coverage. Made with natural materials, which vary in color, and Portland cement, which may effloresce - any implied warranty to the contrary is disclaimed.

PALLET SPEC	S
Pallet Weight	2800 lbs
Sq Ft/Pallet	100 sq.ft.







- Deeply rounded surfaces combine to create the enduring appeal of stone cobbles formed by glaciers and set by hand
- Barreled sidewalls are ideal for decorative curvilinear laying patterns such as fans and circles
- Suitable for medium vehicular applications, such as residential streets and commercial parking lots, with proper pavement design and installation
- Joints and surfaces are designed to create a natural look, minimize furniture wobble, and meet ADA gap and lippage requirements
- Made of durable concrete that won't decay, distort, or attract pests. Iron oxide pigments won't fade with extended UV exposure. Meets or exceeds applicable requirements of ASTM C936 and C1782


STONE(S)

				Rec
	Height	in	ln.	2.36
		mm	MM.	60
	Length	in	IN.	6.77
		mm	MM	172
	Width	in	IN	4.53
		mm	MM	115
	Units	/pl	QTY	490

NOTES

Weights are approximate and do not include shipping pallet. Installation to applicable ICPI standards is required for warranty coverage. Made with natural materials, which vary in color, and Portland cement, which may effloresce - any implied warranty to the contrary is disclaimed.

PALLET LAYOUT



PALLET SPEC	S
Pallet Weight	2884 lbs
Sq Ft/Pallet	103 sq.ft.








- Deeply rounded surfaces combine to create the enduring appeal of stone cobbles formed by glaciers and set by hand
- A variety of shapes provide maximum creative flexibility for decorative installation patterns ranging from fans to bogens
- Suitable for medium vehicular applications, such as residential streets and commercial parking lots, with proper pavement design and installation
- Joints and surfaces are designed to create a natural look, minimize furniture wobble, and meet ADA gap and lippage requirements
- Made of durable concrete that won't decay, distort, or attract pests. Iron oxide pigments won't fade with extended UV exposure. Meets or exceeds applicable requirements of ASTM C936 and C1782

STONE(S)						
				3/4	Trap	Wedge
	Height	in	ln.	2.36	2.36	2.36
		mm	MM.	60	60	60
	Length	in	IN.	3.39	4.06	4.76
		mm	MM	86	103.2	120.9
	Width	in	IN	4.53	4.53	4.53
		mm	MM	115	115	115
	Units	/pl	QTY	280	80	480

PALLET LAYOUT



NOTES

Weights are approximate and do not include shipping pallet. Installation to applicable ICPI standards is required for warranty coverage. Made with natural materials, which vary in color, and Portland cement, which may effloresce - any implied warranty to the contrary is disclaimed.

PALLET SPECS				
Pallet Weight	2520 lbs			
Sq Ft/Pallet	90 sq.ft.			







- Deeply rounded surfaces combine to create the enduring appeal of stone cobbles formed by glaciers and set by hand
- Barreled sidewalls are ideal for decorative curvilinear laying patterns such as fans and circles
- Suitable for medium vehicular applications, such as residential streets and commercial parking lots, with proper pavement design and installation
- Joints and surfaces are designed to create a natural look, minimize furniture wobble, and meet ADA gap and lippage requirements
- Made of durable concrete that won't decay, distort, or attract pests. Iron oxide pigments won't fade with extended UV exposure. Meets or exceeds applicable requirements of ASTM C936 and C1782


STONE(S)

				Twinkie	Square
	Height	in	ln.	2.36	2.36
		mm	MM.	60	60
	Length	in	IN.	2.24	4.53
		mm	MM	57	115
	Width	in	IN	4.53	4.53
		mm	MM	115	115
	Units	/pl	QTY	200	600

NOTES

Weights are approximate and do not include shipping pallet. Installation to applicable ICPI standards is required for warranty coverage. Made with natural materials, which vary in color, and Portland cement, which may effloresce - any implied warranty to the contrary is disclaimed.

PALLET LAYOUT



PALLET SPEC	S
Pallet Weight	2800 lbs
Sq Ft/Pallet	100 sq.ft.







- Deeply rounded surfaces combine to create the enduring appeal of stone cobbles formed by glaciers and set by hand
- Barreled sidewalls are ideal for decorative curvilinear laying patterns such as fans and circles
- Suitable for light vehicular applications, such as residential driveways and parking stalls, with proper pavement design and installation
- Joints and surfaces are designed to create a natural look, minimize furniture wobble, and meet ADA gap and lippage requirements
- Made of durable concrete that won't decay, distort, or attract pests. Iron oxide pigments won't fade with extended UV exposure. Meets or exceeds applicable requirements of ASTM C936 and C1782

STONE(S)

NOTES

\sim	

Weights are approximate and do not include shipping pallet. Installation to applicable ICPI standards is required for warranty coverage. Made with natural

materials, which vary in color, and Portland cement, which may effloresce - any

			Giant Rec
Height	in	ln.	2.36
	mm	MM.	60
Length	in	IN.	10.16
	mm	MM	258
Width	in	IN	6.77
	тт	MM	172
Units	/pl	QTY	200

PALLET LAYOUT



PALLET SPECS Pallet Weight 2688 lbs Sq Ft/Pallet 96 sq.ft.



implied warranty to the contrary is disclaimed.





- Deeply rounded surfaces combine to create the enduring appeal of stone cobbles formed by glaciers and set by hand
- Barreled sidewalls are ideal for decorative curvilinear laying patterns such as fans and circles
- Suitable for medium vehicular applications, such as residential streets and commercial parking lots, with proper pavement design and installation
- Joints and surfaces are designed to create a natural look, minimize furniture wobble, and meet ADA gap and lippage requirements
- Made of durable concrete that won't decay, distort, or attract pests. Iron oxide pigments won't fade with extended UV exposure. Meets or exceeds applicable requirements of ASTM C936 and C1782

STONE(S)

				Twinkie
	Height	in	In.	2.36
		mm	MM.	60
	Length	in	IN.	2.24
		mm	MM	57
	Width	in	IN	4.53
		mm	MM	115
	Units	/pl	QTY	1200

PALLET LAYOUT

NOTES

Weights are approximate and do not include shipping pallet. Installation to applicable ICPI standards is required for warranty coverage. Made with natural materials, which vary in color, and Portland cement, which may effloresce - any implied warranty to the contrary is disclaimed.

PALLET SPECS		
Pallet Weight	2408 lbs	
Sq Ft/Pallet	86 sq.ft.	








- Deeply rounded surfaces combine to create the enduring appeal of stone cobbles formed by glaciers and set by hand
- Barreled sidewalls are ideal for decorative curvilinear laying patterns such as fans and circles
- Suitable for medium vehicular applications, such as residential streets and commercial parking lots, with proper pavement design and installation
- Joints and surfaces are designed to create a natural look, minimize furniture wobble, and meet ADA gap and lippage requirements
- Made of durable concrete that won't decay, distort, or attract pests. Iron oxide pigments won't fade with extended UV exposure. Meets or exceeds applicable requirements of ASTM C936 and C1782

STONE(S)

				3/4
-	Height	in	ln.	2.36
		mm	MM.	60
	Length	in	IN.	3.39
		mm	MM	86
	Width	in	IN	4.53
		mm	MM	115
	Units	/pl	QTY	900

PALLET LAYOUT



NOTES

Weights are approximate and do not include shipping pallet. Installation to applicable ICPI standards is required for warranty coverage. Made with natural materials, which vary in color, and Portland cement, which may effloresce - any implied warranty to the contrary is disclaimed.

PALLET SPECS		
Pallet Weight	2772 lbs	
Sq Ft/Pallet	99 sq.ft.	



