


3" Faircloth Skimmer® Cut Sheet

J. W. Faircloth & Son, Inc.
www.FairclothSkimmer.com



1. Coupling can be removed and hose attached to outlet using the threaded 2" nipple. Typical methods used: on a metal structure a steel stubout welded on the side at the bottom with a 2" threaded coupling or reducers; on a concrete structure with a hole or orifice at the bottom, use a steel plate with a hole cut in it and coupling welded to it that will fit over the hole in the concrete and bolted to the structure with sealant; grout a 4" pvc pipe in a hole in the concrete to connect the skimmer. It can be attached to a straight 4" sch 40 pipe through the dam but the pipe needs to be anchored to the bottom at the connection so it is secure.
2. Dimensions are approximate, not intended as plans for construction.
3. Barrel (solid, not foam core pipe) should be 1.4 times the depth of water with a minimum length of 8' so the inlet can be pulled to the side for maintenance. If more than 10' long weight may have to be added to inlet to counter the increased buoyancy.
4. Inlet tapers down from a 3" maximum inlet to a 2" barrel and hose. Barrel is smaller to reduce buoyancy and tendency to lift inlet but is sufficient for flow through inlet because of slope. The inlet orifice can be reduced using the plug and cutter provided to control the outflow rate.
5. Inlet is 6" pipe between the straps with aluminum screen door for access to the 3" inlet and orifice inside.
6. **Capacity** 9,774 cubic feet per day maximum with 3" inlet and 3" head. Inlet can be reduced by installing a smaller orifice using the plug and cutter provided to adjust flow rate for the particular basin volume and drawdown time required.
7. Shipped assembled. User glues inlet extension and barrel, installs vent, cuts orifice in plug and attaches to outlet pipe or structure. Includes flexible hose, rope, orifice cutter, etc.