



Case Study

application | **Subgrade Stabilization**
location | **Ankeny, IA**
product | **Mirafi® RS580i**

job owner
engineer
contractor
date of installation

Ankeny Centennial High School
Terracon – Des Moines, IA
Stahl Construction
June 2011

TenCate develops and produces materials that function to increase performance, reduce costs and deliver measurable results by working with our customers to provide advanced solutions.

THE CHALLENGE

Ankeny Community School District is building a new high school in Ankeny, a northern suburb of Des Moines, Iowa. Stahl Construction Company has been contracted to build new 50 million dollar high school campus. The new school, named Ankeny Centennial High School, is being constructed over an existing soft subgrade. Flat bed tractor trailers with 20 ton payloads delivering wall panels used to construct the building, along with loaded dump trucks, access the job-site daily.

THE DESIGN

Due to the extremely soft subgrade, an aggregate access road was required for the heavy trucks to gain access to the site. The initial design of the access road included an extruded geogrid placed directly on the subgrade with 6" of aggregate compacted on top of the geogrid. Subgrade pumping occurred due to the heavy truck loading. The geogrid pumped through the aggregate section and severe rutting was experienced. It was determined that separation, filtration and high tensile strength at low strain would be required. The contractor contacted the geotechnical engineer and asked for a new access road design, stating they could not have a failure. Access to the jobsite was critical and could not be interrupted due to rutting.



Mirafi® RS580i being installed over weak subgrade.



Installation complete with 6" aggregate.

THE CONSTRUCTION

The geotechnical engineer recommended a new access road design including TenCate Mirafi® RS580i*, a high strength woven polypropylene geotextile, be placed on the subgrade. The same 6" aggregate section was compacted on top of the Mirafi® RS580i.

THE PERFORMANCE

Fortunately, the benefits of separation, filtration, high tensile modulus and aggregate confinement achieved by Mirafi® RS580i resulted in remarkably improved performance. Access to the jobsite was no longer delayed as rutting no longer occurred. Construction of the new high school was back on schedule.

*Patent Pending



Access road supporting truck traffic.



Concrete pavement installed over Mirafi® RS580i geosynthetic reinforced aggregate.

TenCate Geosynthetics North America assumes no liability for the accuracy or completeness of this information or for the ultimate use by the purchaser. TenCate Geosynthetics North America disclaims any and all express, implied, or statutory standards, warranties or guarantees, including without limitation any implied warranty as to merchantability or fitness for a particular purpose or arising from a course of dealing or usage of trade as to any equipment, materials, or information furnished herewith. This document should not be construed as engineering advice.

Mirafi® is a registered trademark of Nicolon Corporation.

© 2012 TenCate Geosynthetics North America

0412

365 South Holland Drive Tel 800 685 9990 Fax 706 693 4400
Pendergrass, GA 30567 Tel 706 693 2226 www.mirafi.com

