

roughco^{inc}

Environmental Protection & Services



The Pump-It Tube[®] Patent Pending

The Pump-It Tube is ideal for removing sediment when dewatering collection ponds, sumps, and more.

- Attaches easily to pipes and hoses with a Velcro strip (included), simple pipe clamp or heavy zip tie (not included)
- High Flow Grey Material allows 192 gal/ft²/min
- Reusable-After use; clean by spraying out sediment
- Also available in custom sizes depending on amount of discharge
- High strength stitching to minimize high pressure blowouts
- Velcro handles sewn along the length of tube to aide in mobility

The Pumpit Tube[®] Specifications

Minimum Average Fabric Values

Properties

	<u>ASTM TEST</u>	<u>Value</u>
Mass per Unit Area (oz/yd ²)	D-3776	5.2
Grab Tensile Strength, MD x CD (lbs)	D 4632	297 x 223
Grab Elongation, MD x CD (%)	D 4632	58 / 59
Trapezoid Tear, MD x CD (lbs)	D 4533	81 x 75
Puncture (lbs)	D 4833	99
Burst Strength (psi)	D 3786	340
Permittivity (sec-1)	D 4491	2.60
A.O.S. (U.S. sieve – (mm)	D 4751	60
Water Flow Rate (gpm/ft ²)	D-4491	192

Butch Rough (502) 817-1005 – Cell

roughco.com

roughco^{inc}

Environmental Protection
and Services