

TYPAR 3201 & 3301 Specifications

Typar® Professional Landscape Fabric Technical Specifications

Page 1 of 1



PRODUCTS

Typar® Professional Landscape Fabric Specifications

DISTRIBUTOR MAP

WHAT'S NEW

Available in Standard & Heavy Grade Sizes:
3' x 50', 3' x 100', 4' x 50', 4' x 100',
3' x 300', 4' x 300', 75" x 300', 151" x 300'

PRESS RELEASES

REQUEST LITERATURE

Specifications Style 3201 & 3301:
Typar Professional Grade 100% Spunbonded
Polypropylene with UV inhibitors

REQUEST SAMPLES

CONTACT INFO

E-MAIL

SEARCH FOR:

[If you're a homeowner](#)

[If you're a gardening
or landscaping
professional](#)

[Easy installation](#)

PROPERTIES	3201	3301
Unit Weight (oz/yds ²)	1.9	3.0
Tensile Strength(lbs)	73	135
Elongation at Break (%)	>70	>70
Puncture Strength (lbs)	23	35
Air Opening Size (equivalent sieve)	30/40	60/70
Air Opening Size (mm)	0.52	0.24
Trap Tear (lbs)	35	50
Air Permeability (cm/sec)	10x10 ⁻²	3x10 ⁻²
Flux (gal/ft ² /min)	200	70
Permittivity (sec ⁻¹)	3.0	1.2
Thickness	11.5	15.0
Color	Black	Black

DeWitt Company, Inc • 905 South Kingshighway • Sikeston, Missouri 63801