

GHS Safety Data Sheet

PROFILE Products, LLC

ProMatrix®

SDS Number: CON069

Revision Date: 1/1/17

Page 1 of 6

PRODUCT AND COMPANY IDENTIFICATION

Manufacturer

PROFILE Products, LLC 750 LAKE COOK ROAD SUITE 440 BUFFALO GROVE, IL 60089

Emergency:	Emergency Phone: (800) 424-9300 (ChemTrec
Contact:	ChemTrec Acct #: CCN792719
Phone:	(847) 215-1144
Fax:	(847) 215-0577
Email:	tech@profileproducts.com
Web:	www.profileproducts.com

Product Name:	ProMatrix®
Revision Date:	1/1/17
SDS Number:	CON069
CAS Number:	Not applicable
Product Use:	Erosion control and revegetation mulch for hydraulic seeding

Product Description: Green dyed wood fibers, biodegradable fibers, minerals and a proprietary binder mixture.

HAZARDS IDENTIFICATION

Classification of the Substance or Mixture

GHS Classification in Accordance with 29 CFR 1910 (OSHA HCS):

No GHS Classifications Indicated

GHS Label Elements, Including Precautionary Statements

GHS Signal Word: NONE

no GHS pictograms indicated for this product

GHS Hazard Statements:

no GHS hazards statements indicated

GHS Precautionary Statements:

no GHS precautionary statements indicated

Hazards not Otherwise Classified (HNOC) or not Covered by GHS

Route of Entry:	Inhalation, skin contact, eye contact
Inhalation:	Wood may cause sneezing, irritation, and dryness of the nose and throat. Dust may aggravate pre-existing respiratory conditions.
Skin Contact:	Wood dust can cause irritation. Skin absorption is not known to occur.
Eye Contact:	Wood dust can irritate the eyes.
Ingestion:	No reports of human ingestion.

OSHA Classification: Wood dust is a hazardous substance as defined by the Hazard Communication Standard 29CFR 1910.1200



GHS Safety Data Sheet

PROFILE Products, LLC

ProMatrix®

SDS Number: CON069

Revision Date: 1/1/17

Page 2 of 6

NFPA: Health = 1, Fire = 1, Reactivity = 0, Specific Hazard = n/a



COMPOSITION/INFORMATION OF INGREDIENTS

Ingredients:

Cas# % Chemical Name

0 Proprietary Hydrocolloidal Based Polysaccharide Tackifier

9000300 Proprietary Guar Gum

4 FIRST AID MEASURES Inhalation: Usually not a problem. Remove to fresh air if respiratory irritation develops, and get medical aid promptly if irritation persists. In high dust levels wear dust mask. Skin Contact: Usually not a problem. Wash off with running water if irritation is experienced. Eye Contact: Open eyelids and flush with water. Ingestion: Get medical attention.

FIRE FIGHTING MEASURES

Flammability:	Combustible product
Flash Point:	Not applicable
Flash Point Method:	Not applicable
Autoignition Temp:	200-260°C (400-500°F)

Conditions to avoid: In contact with flames or hot surfaces

Flammable- Extinguish with water; same as a wood fire

ACCIDENTAL RELEASE MEASURES

Scoop up product. Wear goggles and respirator if dust is produced in unventilated areas. Wet product will be slippery.

7 HANDLING AND STORAGE

Handling Precautions:Clean up areas where dust settles. Minimize blowdown or other practices that generate high airborne
dust concentrations.Storage Requirements:Store in a cool, dry place. Keep away from sources of ignition.



GHS Safety Data Sheet

PROFILE Products, LLC

ProMatrix®

SDS Number: CON069

Revision Date: 1/1/17

Page 3 of 6

EXPOSURE CONTROLS/PERSONAL PROTECTION

Engineering Controls:	None required for outdoor mixing and application. Use dust collection system for indoor handling operations.
Personal Protective Equipment:	Eye Protection: Wear goggles when emptying bags and during other operations where there is a risk of dust entering the eyes. Gloves: Leather, plastic or rubber gloves could be worn to minimize skin irritation. Respirators: When handling methods generate dust at concentrations that exceed occupational exposure limits, wear a NIOSH approved respirator. A fabric respirator or a facepiece respirator with dust cartridges will generally provideadequate protection. Footwear: The product is slippery when wet. Wear appropriate footwear.

9	PHYSICAL AND CHEMIC	CAL PROPERTIES		
Appearance: Physical State: Spec Grav./Density: Vapor Pressure:	Dyed green wood fibers - Pine Wood Fibers Lighter than water N/A	& mixed hardwoods Odor:	Mild wood odor	

10	STABILITY AND REACTIVITY	
Chamies I Stability	Otable preduct	

Chemical Stability:	Stable product
Conditions to Avoid:	Contact with strong acids and oxidizers may generate heat. Product may ignite at temperatures in excess of 200°C (400°F).
Materials to Avoid:	Strong acids and oxidizers
Hazardous Polymerization:	Will not occur.

TOXICOLOGICAL INFORMATION

EFFECTS OF CHRONIC EXPOSURE:

Inhalation: Frequent and repeated exposure to wood dust is associated with an increased risk of developing nasal cancer. Skin Contact: Although rare, wood dust may cause dermatitis in sensitized people.

Occupational Exposure Limits:

Wood dusts- All other species: ACGIH (2007): TLV-TWA 1 mg/m³ (Inhalable fraction); A4 Particulates Not Otherwise Regulated (PNOR): OSHA: PEL-TWA 15 mg/m³ (Total Dust); 5 mg/m³ (Respirable fraction)

Irritancy: Wood dust is a mild irritant Sensitization: Some wood dusts may cause allergic skin reactions



GHS Safety Data Sheet

PROFILE Products, LLC

ProMatrix®

SDS Number: CON069

Revision Date: 1/1/17

Page 4 of 6

ECOLOGICAL INFORMATION

SDS


Guar Gum (CAS# 9000-30-0) is listed as an inert ingredient permitted for use in nonfood use pesticide products by EPA. It is also classified under the Federal Insecticide, Fungicide and Rodenticide Act (FIFRA) as a minimal risk inert substance (List 4A) meaning that as a pesticide, Guar Gum is considered by the EPA to pose little or no risk to humans or the environment. The Us Department of Agriculture (USDA) National Organic Program (NOP) also allows the use of Guar Gum in a variety of applications, but primarily as a pesticide in organic production operations. Finally, Guar Gum is listed on the Generally Recognized as Safe (GRAS) list by the Food and Drug Administration (FDA).

48-hr $LC_{50} = >100\%$ for Daphnia magna when runoff generated using ASTM D7101 (2"/hr rainfall rate) was tested according to EPA-821-R-02-012.

DISPOSAL CONSIDERATIONS

Normally can be disposed of as a wood residue. Ensure disposal is in compliance with local, provincial (state), and federal regulations.

14 TRANSPORT INFORMATION



PROFILE Products, LLC

ProMatrix®

SDS Number: CON069

Revision Date: 1/1/17

Page 5 of 6

REGULATORY INFORMATION

SDS

Component (CAS#) [%] - CODES

Hydrocolloidal Based Polysaccharide Tackifier (0) [Proprietary]

Guar Gum (9000300) [Proprietary] TSCA

Regulatory CODE Descriptions

TSCA = Toxic Substances Control Act

COMPONENT / (CAS/PERC) / CODES

*Guar gum (9000300 n/a%) TSCA

REGULATORY KEY DESCRIPTIONS

MASS = MA Massachusetts Hazardous Substances List NRC = Nationally Recognized Carcinogens OSHAWAC = OSHA Workplace Air Contaminants PA = PA Right-To-Know List of Hazardous Substances TXAIR = TX Air Contaminants with Health Effects Screening Level

CERCLA = Superfund clean up substance CSWHS = Clean Water Act Hazardous substances EHS302 = Extremely Hazardous Substance EPCRAWPC = EPCRA Water Priority Chemicals HAP = Hazardous Air Pollutants NJEHS = NJ Extraordinarily Hazardous Substances NJHS = NJ Right-to-Know Hazardous Substances OSHAPSM = OSHA Chemicals Requiring process safety management SARA313 = SARA 313 Title III Toxic Chemicals

TSCA = Toxic Substances Control Act





GHS Safety Data Sheet

PROFILE Products, LLC

ProMatrix®

SDS Number: CON069

Revision Date: 1/1/17 Page 6 of 6

16

OTHER INFORMATION

Disclaimer:

Although reasonable care has been taken in the preparation of this document, we extend no warranties and make no representations as to the accuracy or completeness of the information contained herein, and assume no responsibility regarding the suitability of this information for the user's intended purposes or for the consequences of its use. Each individual should make a determination as to the suitability of the information for their particular purpose(s).

LOCATIONS & CONTACT INFO

ASP ENTERPRISES

aspent.com salesasp@aspent.com

St. Louis, MO 636.343.4357

Kansas City, MO 816.554.1191 **Omaha, NE** 402.861.8579 **Wichita, KS**

Enterprises

Wichita, KS 316.393.1554

BOWMAN CONSTRUCTION SUPPLY

bowmanconstructionsupply.com quicksupplyco.com salesbcs@bowmanconstructionsupply.com salesquick@quicksupplyco.com

Denver, CO Loveland, CO 303.696.8960 970.535.0863

Bowman Construction

Supply Inc.

Colorado Springs, CO 719.257.7840 QUICK SUPPLY CO. quicksupplyco.com

quick@quicksupplyco.

Quick Supply Co.

> **Des Moines, IA** 515.289.1271

CASCADE GEOSYNTHETICS cascadegeos.com

salescascade@cascadegeos.com

Portland, OR 971.339.1020

Salt Lake City, UT 435.276.0820

SOLUTIONS WE SUPPLY

GEOSYNTHETICS

Filter Fabrics

Stabilization Fabrics Geogrids

- Road Grids
- Wall Grids
- Slope Stabilization
- Specialty Fabrics

Composite Geomembranes

• GCLs, PVC, HDPE, LLDPE, EPDM, Granular Bentonite

SEDIMENT CONTROL

Inlet Protection

Grated Inlet, Curb Inlet, Area Inlet
 Protection

Ditch Checks

- Triangle Silt Dike
- GeoRidge

Perimeter Protection

- High and Low-Porosity Silt Fence, Straw Wattles, Silt Socks
- Safety Fence

Flocculants & Water Treatment

Polymer-Based & Natural Flocculants
 Sediment Basin Skimmers
 Dewatering Bags

Trackout Control

- FODS
- Rumble Grates

Turbidity Curtains

EROSION CONTROL

Basic Hydraulically Applied Mulches

- Wood
- Paper
- Blends
- Straw

High-Performance Hydraulically

- **Applied Products**
 - BFM
 - FGM
 - Additives & Tackifiers

Temporary Erosion Control Blankets

- Coir & Jute Mat/Nettings
- Short-Term ECBs
- Extended-Term ECBs

Permanent Erosion Control Blankets

- Turf Reinforcement Mats
- HP-TRMs
- Anchor Reinforced Vegetation System

Structural BMPs

- Transition Mats
- Geoweb Cellular Confinement
- Composite Vegetated Armor System
- Flex MSE Vegetated Wall System
- Articulated Concrete Block
- Gabions
- Grout-Filled Geotextile Mats

We are full line distributors of construction materials for all project types. Contact us for assistance with a project. From specification and development to installation and completion, we're here to help with all of your site solution needs.

GEOSYNTHETICS | EROSION CONTROL | STORMWATER MANAGEMENT SEDIMENT CONTROL | REVEGETATION & SOIL AMENDMENTS

Vegetation Establishment

- Native Seed & Turf Seed
- Fertilizers
- Organic Soil Additives
 Stratavault Soil Cells

STORMWATER MANAGEMENT

Water Quality

- Inlet Filter Boxes
- Pre-Treatment Chamber
- Nutrient Separating Baffle Boxes
- High-Flow Biofiltration MediaHydrodynamic Separators
- HydrodynaStratavault

Water Quantity

- Modular Underground Storage
 Systems
- Chamber Detention Systems

Drainage

- HDPE Swale Liner
- Pipe & Fittings
- Drainage Composites
- Strip Drain

Inlet Structures

- PVC
- Drain Basis, In-Line Drains
- Landscape

Permeable Pavers

- Permeable Articulating Concrete Block
- Grass Pavers
- Gravel Pavers
- Concrete Pavers

SPECIALTY

Natural & Synthetic Coir Fiber Logs Vegetated Reinforced Soil Slopes Soil Anchors Root Barrier System AquaBlok Muscle Wall